

Installation cable Meridian Install SP225 CPR- Version; 2 x 2,50 mm²; FRNC Ø 8,20 mm; black; Cca

Art. No.: 425-0051FC

ANALOG FRNC HALOGEN-FREE OFC



General Data

Article number :	425-0051FC
Name :	Meridian Install SP225 CPR- Version
EAN :	4049371375320
Properties :	OFC oxygen free copper
Properties :	FRNC flame retardant
Properties :	Halogen-free / LSZH
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application area :	Studio / Broadcast
Application :	Installation cable
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Cca

Technical Data

Construction :	(2LIY2,5mm ²)Y
Jacket material :	FRNC
Jacket Ø [mm] :	8,20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	2,50
Inner conductor Ø (audio) [mm] :	1,78
AWG (audio) :	13
Copper strands (audio) :	50
Copper strand Ø (audio) [mm] :	0,25
Conductor insulation Ø [mm] :	3,05
UV-resistant :	yes
Fire load per m [kWh] :	0,38
Style variant :	round
Packing :	500 m spool
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	8,2
[mm] :	8,2

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	136
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	7,5