



ASSEMBLY INSTRUCTION

etherCON® TOP | NE8MX-TOP

Ruggedized RJ 45 Data Connector, IP65 and UL50E



IP65 RATED AND UL50E APPROVED.

MOUNTING VERSIONS

1 & **3** STANDARD ASSEMBLY OF etherCON CONNECTOR


2 & **3** WITH ASSESSORIES:
CABLE & BOOT ASSEMBLY WITH INSERTION TOOL.
ITX-TOP: Cable insertion tool to guide the cable into the boot.



1 STANDARD CABLE ASSEMBLY




A Cut cable end approx. 45°.




B Slide the bushing over the cable.

To ease the boot assembly apply some cable pulling lubricant to the cable ends.

2 CABLE & BOOT ASSEMBLY WITH INSERTION TOOL





A Position the Insertion Tool onto the cable.







B Wet the tip with mounting fluid.



- C**  **C** Slide the cable with the tool through the boot.
- D**  **D** Remove the tool.

3 ASSEMBLY RJ45 PLUG AND CONNECTOR


- A**  **A** Assemble the RJ45 plug on the cable.
- A1**  **A1** Cut off the release tab of RJ45 plug.
- B**  **B** Put the chuck onto the cable. Align the opening with the contact side.




- C** Position the RJ45 in the chuck.

Attention:

- 1** RJ45 must be straight.
- 2** Special versions must engage in the inner recess of the chuck.



D Position the bushing onto the chuck.



E Slide the unit (insert and boot) into the housing and tighten the bushing.

Attention:
Screw the bushing to the end of the thread.



F CAUTION:

There is no overlap allowed.

✓ FINISHED etherCON®



Find more etherCON® details on www.neutrik.com.



ITX-TOP TOOL:
Find more details on www.neutrik.com/product/itx-top



NEUTRIK AG	LI	T: +423 / 237 24 24	F: +423/232 53 93	NEUTRIK France	FR	T: +33 1/4131 6750	F: +33 1/4131 0511
NEUTRIK USA Inc.	USA	T: +1 704 / 972 3050	F: +1 704/438 9202	NEUTRIK Tokyo Ltd.	JP	T: +81 3/3663 4733	F: +81 3/3663 4796
NEUTRIK (UK) Ltd.	UK	T: +44 1983 / 811 441	F: +44 1983/811 439	NEUTRIK Hong Kong Ltd.	HK	T: +852/2687 6055	F: +852/2687 6052
NEUTRIK Vertriebs GmbH	DE/NL/AT/DK	T: +49 8131 / 280 890	F: +49 8131/280 830	NEUTRIK India Pvt. Ltd.	IND	T: +91/982 05 43 424	F: +91/22 26163 540

Draft. Nr.: BDA 547 V2 | Update: 28.11.2019 | Data subject to change without prior notice. ©2019 NEUTRIK®. ALL RIGHTS RESERVED. NEUTRIK® are registered trademark.