


NF-Phono cable, HighEnd SC-Albedo MKII; 2 x 0,20 mm²; PVC Ø 5,90 mm; green

Art. No.: 800-0104

ANALOG

OFC



General Data

Article number :	800-0104
Name :	SC-Albedo MKII
EAN :	4049371003223
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application :	NF-Phono cable, HighEnd
Colour :	green
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,20mm ²)(ST)DY
Jacket material :	PVC
Jacket Ø [mm] :	5,90
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,20
AWG (audio) :	24
Shielding :	Copper spiral sleeve + AL / PT foil
Shielding factor [%] :	100
Copper strands (audio) :	102
Copper strand Ø (audio) [mm] :	0,05
Conductor insulation material :	PP
Weight per 1 m [g] :	32
Fire load per m [kWh] :	0,13
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	5,9
[mm] :	5,9

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	65
Capac. cond./shield. per 1 m (audio) [pF] :	110
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	148
Shield. resistance per 1 km [Ω] :	30