


# Instrument Cable SC-Sinus Control; 1 x 2 x 0,35 mm<sup>2</sup>; 1 x control; PVC; 15 x 6,2 mm; blue

Art. No.: 320-0252

ANALOG

OFC



## General Data

Article number :	320-0252
Name :	SC-Sinus Control
EAN :	4049371002103
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Instrument Cable
Colour :	blue
BPVo-Euroclass :	Fca

## Technical Data

Signal transmission :	asymmetrical
Construction :	LI2Y(ST)CY2x0,35mm <sup>2</sup> +1x0,35mm <sup>2</sup>
Construction (audio) :	LI2Y(ST)CY2x0,35mm <sup>2</sup>
Construction (control) :	1 x 0,35 mm <sup>2</sup>
Jacket material :	PVC
Number of Channels (audio) :	1
Number of Channels (control) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	0,35
Inner conductors (control) [mm <sup>2</sup> ] :	0,35
Inner conductor Ø (audio) [mm] :	0,67
Inner conductor Ø (control) [mm] :	0,67
AWG (audio) :	22
AWG (control) :	22
Shielding (audio) :	Copper braiding + AL / PT foil
Shielding factor [%] :	100
Copper strands (audio) :	11
Copper strands (control) :	11
Copper strand Ø (audio) [mm] :	0,20
Copper strand Ø (control) [mm] :	0,20
Wire insulation material (audio) :	Foam / Skin-PE
Conductor insulation Ø (audio) [mm] :	3,00
Weight per 1 m [g] :	86
Fire load per m [kWh] :	0,26
Style variant :	twin
Packing :	100 m spool
Packing :	50m spool
Temperature min. [°C] :	-20
Temperature max. [°C] :	70
Width [mm] :	15

Height [mm] : 6,2

## Electrical Data

Capac. cond./shield. per 1 m (audio) [pF] :	75
Insulation resist. per 1 km [GΩ] :	0
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km (audio) [Ω] :	53